



SECTION A - A

NOTES:

1. THIS STANDARD IS TO BE IN ACCORDANCE WITH SCHEDULE "B" OF THE SITE ALTERATION BY-LAW, "CODE FOR THE DESIGN AND MAINTENANCE OF EROSION AND SEDIMENTATION CONTROL MEASURES" AND IS TO BE ADMINISTERED ACCORDINGLY.
2. SEDIMENT SHALL BE REMOVED AND TRAP RESTORED TO ITS ORIGINAL DIMENSIONS WHEN THE SEDIMENT HAS ACCUMULATED TO 1/2 THE DESIGN DEPTH OF THE TRAP. REMOVED SEDIMENT SHALL BE DEPOSITED IN A SUITABLE AREA IN SUCH A MANNER THAT IT WILL NOT ERODE. THE STRUCTURE SHALL BE INSPECTED AFTER EACH RAIN AND REPAIRS MADE AS NEEDED. CONSTRUCTION OPERATIONS SHALL BE CARRIED OUT IN SUCH A MANNER THAT EROSION AND WATER POLLUTION IS MINIMIZED.
3. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SHOWN.

CITY OF BARRIE STANDARD				APR'D: R.G.N.	DATE: 04.03.16
TYPICAL GRANULAR EROSION CONTROL DEVICE		2	MODIFICATIONS BY ENV. SER.	2004.04.06	DRAWN: L.A.J.
		1	TRENCH ADDED AND FABRIC EXTENDED INTO IT	B.R. 2003.02.19	SCALE: N.T.S.
		NO.	REVISION	APR'D	DATE
					BSD-23B