



1. ALL LUMBER TO BE PRETREATED WITH AN APPROVED BROWN, MICRONIZED COPPER WOOD PRESERVATIVE OR APPROVED EQUIVALENT.
2. FENCE LOCATIONS AND DIMENSIONS MUST BE IN ACCORDANCE WITH APPLICABLE LANDSCAPE LAYOUT AND APPROVED DRAWINGS.
3. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS NOTED.
4. ALL HARDWARE TO BE HOT DIP GALVANIZED.
5. DETAIL TO BE USED IN CONJUNCTION WITH BSD-1205 AND BSD-1206.

38 x 89 MIDDLE SUPPORT RAIL , FASTEN TO POST WITH GALVANIZED HANGERS (see Fig. 1)

38 x 89 LOWER SUPPORT RAIL TO REMAIN PARALLEL WITH THE GROUND, FASTEN TO POST WITH GALVANIZED HANGERS (see Fig. 1)

NOTE: FOR FENCE INSTALLATION AND FOOTING SPECIFICATIONS REFER TO BSD-1200 AND BSD-1201

The City of
BARRIE
STANDARD DETAIL

RESIDENTIAL TO RESIDENTIAL
BOARD FENCE
SLOPE ACCOMMODATION

REV No.	DATE: JUNE 2015
1	SCALE: N.T.S.

BSD-1207

APPROVED
DATE: June 11/15
.....
DIRECTOR OF ENGINEERING