



CEDAR FENCE POST TO BE PLACED AT EACH TERMINUS OR CHANGE OF DIRECTION, POSTS ARE TO BE DIRECT BURIED WITH A MINIMUM 1000 EMBEDMENT

NOTE: CEDAR POSTS ARE REQUIRED WHERE FENCE LENGTHS EXCEED 150 LINEAR METERS AND ARE NOT REQUIRED WITHIN THE MUNICIPAL BOULEVARDS

NOTE: FENCE MUST BE TENSIONED AND SECURED BACK ON ITSELF WITH A SINGLE WRAP AROUND THE TERMINAL POST

150mm (0'-6") PAGE WIRE FENCING

50 x 50 x 1800 STEEL 'T' BAR POSTS SPACED 2400 ON CENTRE, TOP 200mm TO BE PAINTED WITH FLORESCENT YELLOW OR ORANGE PAINT

TREE PRESERVATION NOTIFICATION SIGNAGE PLACED ALONG LENGTH OF FENCE AT 50 METER INTERVALS. REFER TO DETAIL BSD-1231

1. THIS DETAIL IS USED IN CONJUNCTION WITH BSD-1233 -SEDIMENTATION CONTROL FENCE.
2. PAGE WIRE FENCE TO BE ATTACHED TO CEDAR RAIL POSTS WITH 'U' SHAPED GALVANIZED NAILS ON EACH HORIZONTAL STRAND.
3. USE A MINIMUM OF FOUR (4) 100MM, 16 GAUGE GALVANIZED T-POST CLIPS TO ATTACH PAGE WIRE FENCE TO EACH 'T' BAR POST.
4. 'T' BARS ARE TO BE DRIVEN INTO THE GROUND TO A MINIMUM DEPTH OF 600mm.
5. ALL MEASUREMENTS ARE IN MILLIMETRES UNLESS OTHERWISE NOTED.
6. THIS DETAIL TO BE USED IN CONJUNCTION WITH BSD-1230, BSD-1231, BSD-1234 AND BSD-1235.