



1. MINIMUM SETBACK FROM PROPERTY LINES FOR ASPHALT PLAY SURFACE IS 15000.
2. PLAY OUT ZONE TO REMAIN CLEAR OF PHYSICAL ENCROACHMENTS.
3. BASKETBALL POSTS ARE TO BE CANTILEVERED OVER THE PLAY SURFACE.
4. ALL LINES TO BE COMPRISED OF WHITE TRAFFIC PAINT AS PER O.P.S.S. 710.
5. PROVIDE A MAXIMUM GRADE OF 1.0% ACROSS ASPHALT COURT.
6. PROVIDE A MAXIMUM GRADE OF 2.0% FOR PLAY OUT ZONE.
7. ALL DIMENSIONS ARE IN MILLIMETRES.
8. DETAIL TO BE USED IN CONJUNCTION WITH BSD-1292, BSD-1293 AND BSD-1294.

**APPROVED**

DATE: *June 11/15.*

*AMU*

DIRECTOR OF ENGINEERING

The City of  
**BARRIE**  
STANDARD DETAIL

**BASKETBALL  
FULL COURT LAYOUT**

REV No. 1 DATE: JUNE 2015  
SCALE: N.T.S.

**BSD-1291**  
FORMERLY BSD-58