


MODIFIED ROLLOVER CURB DETAIL



MODIFIED ROLLOVER CURB NOTES:

- TOP EDGES OF CURB AND GUTTER TO BE ROUNDED USING AN APPROVED EDGING TOOL.
- ALL CONCRETE WORK TO CONFORM TO ONTARIO PROVINCIAL SPECIFICATIONS & STANDARDS (OPSS).
 - CLASS OF CONCRETE: 30MPa
- 4. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SHOWN
- ALL DRIVEWAY & SIDEWALK RAMPS TO BE DESIGNED AND CONSTRUCTED TO APPLICABLE ONTARIO PROVINCIAL STANDARDS AND CITY OF BARRIE STANDARDS.

UNDER REVIEWNovember 2023

NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SHOWN.
- 2. WASTEWATER SYSTEMS, STORMWATER SYSTEMS, AND WATER DISTRIBUTION AND TRANSMISSION SYSTEMS TO BE DESIGNED IN ACCORDANCE WITH CITY OF BARRIE INFRASTRUCTURE STANDARDS.
- 3. REFER TO THE CITY OF BARRIE ROADWAY LIGHTING POLICIES IN THE RIGHT-OF-WAY INFRASTRUCTURE STANDARD AND ASSOCIATED STANDARD DRAWINGS FOR LIGHT STANDARD AND POLE BASE LOCATION AND DEPTH.
- 4. REFER TO RIGHT-OF-WAY INFRASTRUCTURE STANDARD FOR PAVEMENT DESIGN METHODOLOGY.
- TREE/LANDSCAPING ARE TO BE ACCOMMODATED WHEREVER POSSIBLE IN LOCATIONS APPROVED BY THE PARKS, PLANNING, AND DEVELOPMENT BRANCH AND IN ACCORDANCE WITH CITY OF BARRIE GUIDELINES.
- TYPICAL MINIMUM DEPTH FOR UTILITY CROSSINGS SHALL BE 1.0m (TO CLEAR SUBDRAINS).



CROSS-SECTION 12.0m LANEWAY REV No.

DATE: APR 2023

SCALE: N.T.S.

R314