



### LUMINAIRE SPECIFICATIONS

MOUNTING METHOD: POST TOP  
 OPTICAL SYSTEM: GLOBE BRUSHED FINISH (GPB)  
 LIGHT SOURCE: LED  
 CCT: 3000K  
 LINE VOLTAGE: 120V  
 PAINT: BLACK  
 OPTIONS: #5 FINIAL, TWISTLOCK RECEPTACLE, DECORATIVE CAP AND DECORATIVE DONUT (PHOTO CELL BY OTHERS)

### OPTIONS:

QUICK DISCONNECT   
 TERMINAL BLOCK   
 OTHERS -

### NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN.
2. FOR POLE DETAILS, SEE R337.
3. THE CITY SHALL SUPPLY THE POLE ID PLATE(S) AND THE CONTRACTOR SHALL SUPPLY THE STAINLESS STEEL STRAPPING NECESSARY FOR MOUNTING. THE CONTRACTOR SHALL CO-ORDINATE THE SUPPLY OF THE POLE ID PLATE(S) WITH THE CITY OF BARRIE'S TRAFFIC SERVICES DEPARTMENT. POLE ID PLATE(S) SHALL BE INSTALLED AS PER THE CONTRACT DRAWING AND AS DIRECTED BY THE CONTRACT ADMINISTRATOR IN CONSULTATION WITH TRAFFIC SERVICES.
4. POLE ID PLATE(S) SHALL BE MOUNTED HIGHER IF THE VIEW OF THE PLATE IS OBSTRUCTED.



DECORATIVE CONCRETE POLE  
WITH POST TOP LUMINAIRE

REV No. DATE: APR 2024

5

SCALE: N.T.S.

R336