



Notes:

1. ALL DIMENSIONS ARE MILLIMETRES UNLESS OTHERWISE SHOWN.
2. BANDING SHALL BE FLUSH ON EITHER SIDE OF THE CYCLE TRACK SHALL BE 200mm STAMPED CONCRETE WITH TRANSVERSE SCORE LINES AT 200mm INTERVALS. MINIMUM LATERAL CLEARANCE OF 300mm FROM EDGE OF BANDING TO BE MAINTAINED OF ANY VERTICAL OBSTRUCTIONS.
3. LINE PAINTING SHALL BE INSTALLED IN ACCORDANCE WITH OTM BOOK 11 AND OTM BOOK 18.
4. TWSI'S SHALL MATCH CURB RADIUS.
5. SIGHT TRIANGLES SHALL BE 7.0m BY 7.0m IN ACCORDANCE WITH CITY OF BARRIE STANDARD DETAIL R323.
6. SIGNAL DESIGN REQUIREMENTS SHALL BE IN ACCORDANCE WITH CITY OF BARRIE STANDARD DETAILS R349 AND R365.
7. RA-16 SHALL ADHERE TO OTM BOOK 18 REQUIREMENTS.
8. A MINIMUM 500MM CLEAR ZONE BETWEEN THE SIDEWALK AND PROPERTY LINE SHALL BE MAINTAINED OF ANY VERTICAL OBSTRUCTIONS.



**INTERSECTION
MAJOR COLLECTOR - MAJOR COLLECTOR**

REV No. 1	DATE: APRIL 2024 SCALE: N.T.S.
---------------------	-----------------------------------

R364